


Fiber Coupled VCSEL Array Module (30W)
Part # PCW-M04-30-W1064
(Preliminary)

- Vertical-Cavity Surface-Emitting Laser technology
- Power output of 30W from 400u 0.4NA fiber
- Consists of several hundred single mode VCSEL devices
- CW, pulse and QCW operation
- Custom wavelengths available (808-1064nm)



Optical & Electrical Characteristics


PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
CW Output Power	150A, 25C Heat-sink	30	40	--	W
Threshold current	25C Heat-sink	--	10	15	A
Operating current	30W, 25C Heat-sink	--	135	150	A
Operating voltage	30W, 25C Heat-sink	--	2	2.4	V
Differential resistance	30W, 25C Heat-sink	--	5.8	7.0	mΩ
Center wavelength	30W, 25C Heat-sink	1050	1064	1080	nm
Spectral width (FWHM)	30W, 25C Heat-sink	--	0.8	1	nm
Wavelength shift	25C Heat-sink	0.060	0.065	0.070	nm/°C

Copyright © 2009 Princeton Optronics, Inc.
All Rights Reserved.

Princeton Optronics reserves the right to change product design and specifications at any time without notice.

No license is granted by implication or otherwise under any patents or patent right of Princeton Optronics. No responsibility is assumed for the use of these products, nor for any infringement on the rights of others resulting from the use of these products

Laser diode product components are intended for use in a user-devised end system. However, these products are capable of emitting Class IV radiation. Extreme care must be exercised during their operation. Only persons familiar with the appropriate safety precautions should operate a laser product. Directly viewing the laser beam or exposure to specular reflections must be avoided. Serious injury may result if any part of the body is exposed to the beam. The eye is extremely sensitive to the infrared radiation and therefore, proper eye-wear must be worn at all times. Use of optical instruments with these products may increase eye hazard. Always wear eye protection when operating.



REV. A – 03/09

Princeton Optronics, Inc. * 1 Electronics Drive * Mercerville, New Jersey 08619

Voice: (609) 584-9696 * Fax: (609) 584-2448 * E-mail: sales@princetonoptronics.com * www.princetonoptronics.com