


100W 808nm VCSEL Array Submodule PQCW-CS1-100-W0808

- Vertical-Cavity Surface-Emitting Laser technology
- Very high reliability
- High temperature operation (up to 80°C)
- Wavelength stabilized & narrow spectral width (~ 1 nm)



Optical & Electrical Characteristics


PARAMETER	CONDITIONS*	MIN	TYP	MAX	UNIT
QCW Output power	120A, 25°C Heat-sink	100	120	--	W
Threshold current	25°C Heat-sink	--	15	22	A
Operating current	P _{out} , 25°C Heat-sink	--	100	120	A
Operating voltage	P _{out} , 25°C Heat-sink	--	2.9	3.2	V
Differential resistance	P _{out} , 25°C Heat-sink	--	14	17	mΩ
Slope efficiency	25°C Heat-sink	1	1.1	--	W/A
Conversion efficiency	40W, 25°C Heat-sink	40	45	--	%
Center wavelength	P _{out} , 25°C Heat-sink	800	808	816	nm
Spectral width (FWHM)	P _{out} , 25°C Heat-sink	--	1	2	nm
Wavelength shift	25°C Heat-sink	--	--	0.07	nm/°C
N.A. (4 sigma)	P _{out} , 25°C Heat-sink	--	0.18	0.2	--
Emission area	--	--	4.7 x 4.7	--	mm ²

* QCW conditions: 100 μsec pulse-width / 0.3% duty cycle (30Hz)

Maximum Absolute Ratings


PARAMETER	CONDITIONS
Forward current	150 A
Reverse current	25 μA
Operating temperature	0 to +80 °C
Storage temperature	-40 to +80 °C
Pulse width/duty-cycle	200 μsec / 2%

Ordering information



Mechanical Characteristics

PARAMETER	CONDITIONS
Package width	8.47 ± 0.01 mm
Package length	12.70 ± 0.01 mm
Package height	0.60 ± 0.01 mm
Thermal resistance	< 0.3 °C/W
Max solder temperature	140 °C
Metallization	Ti/Pt/Au + 12 μm Au



- NOTES:
 1. ANODE AND CATHODE METALLIZATION: Au PLATING FOR WIREBONDING AND SOLDERING.
 2. FULL BACKSIDE METALLIZATION: Au PLATING FOR SOLDERING.
 3. WIREBONDS SHOWN FOR INFORMATION ONLY.
 4. WIREBOND SIZE, NUMBER AND CONFIGURATIONS MAY VARY.
 5. SUBSTRATE THICKNESS.

Copyright © 2009 Princeton Optronics, Inc.
All Rights Reserved.

Princeton Optronics reserves the right to change product design and specifications at any time without notice.

No license is granted by implication or otherwise under any patents or patent right of Princeton Optronics. No responsibility is assumed for the use of these products, nor for any infringement on the rights of others resulting from the use of these products

Laser diode product components are intended for use in a user-devised end system. However, these products are capable of emitting Class IV radiation. Extreme care must be exercised during their operation. Only persons familiar with the appropriate safety precautions should operate a laser product. Directly viewing the laser beam or exposure to specular reflections must be avoided. Serious injury may result if any part of the body is exposed to the beam. The eye is extremely sensitive to the infrared radiation and therefore, proper eye-wear must be worn at all times. Use of optical instruments with these products may increase eye hazard. Always wear eye protection when operating.



REV.C- 8/16